



Optional Hose Reel

Community Design No: 000235429
 UK Registered Design No: 2098802

Features / Benefits

- Direct PTO drive
- Stand attaches to 3-point linkage
- Suction or Direct Feed
- Triple Piston Cat Pump 
- Metered chemical system
- Thermo sensor valve
- Protects pump from overheat
- Optional Hose Reel (shown above)

30KPTO	
Max Pressure:	3000 PSI / 207 BAR
Volume:	1000 RPM - 6.0 GPM / 27.3 LPM 540 RPM - 3.3 GPM / 15 LPM
Pump:	Triple piston Cat Pump
Engine:	N/A
Drive:	PTO
Supply:	Suction or Direct Feed
Suction Hose:	4.5m 3/4" hose with stainless steel suction strainer
Delivery Hose:	15m 3/8" braided with Quick Screw adaptor
Gun:	With swivel coupling and Quick Screw adaptor
Lance:	1m two piece stainless steel lance
Nozzle:	NZ15045 - 540 RPM NZ1508 - 1000 RPM
Fuel Consumption:	N/A
Thermo-sensor valve:	Protects pump from re-circulation overheat
Chemical System:	Metered high pressure chemical system with chemical inlet hose and filter (only operates with suction feed)



Specification may differ per country. Brendon reserves the right to alter the specification without notice.



Sandblasting



Drain Jetting



Mobile Reel



Gulper Kit